

DRILL PIPE PROTECTOR « SLICK » Type Clearance Chart

DRILL PIPE (I.F.)	BORE AREA		2 7/8		3 1/2		4		4 1/2		5		5 1/2		6 5/8								
	1.750 2.410	2.125 3.976	4 1/4	5	4 3/4	5	5 1/4	5 1/2	5 3/4	6	6 1/4	6 1/2	6 3/4	7	7 1/4	7 1/2	7 3/4	8	8 1/2	8 3/4	9		
PROTECTOR →	3 3/8	3 7/8	4 1/4	4 3/8	4 1/2	4 3/4	5	5 1/4	5 1/2	5 3/4	6	6 1/4	6 1/2	6 3/4	7	7 1/4	7 1/2	7 3/4	8	8 1/2	8 3/4	9	
AREA SQ. INS.	8.95	11.79	14.19	15.03	16.35	17.72	20.63	21.65	23.76	25.97	28.27	30.68	33.18	35.79	38.49	41.18	44.18	47.17	50.27	53.46	56.75	60.12	63.62
WT	15.10	3.826	11.50																				
I.D.	AREA																						
4 1/2																							
5																							
5 1/2																							
6																							
6 5/8																							
7																							
7 5/8																							
8 5/8																							
24.00	8.097	51.50																					
28.00	8.017	50.48																					
32.00	7.921	49.28																					
36.00	7.825	48.10																					
40.00	7.725	46.87																					
44.00	7.625	45.66																					
48.00	7.511	44.30																					
52.00	7.394	42.81																					
56.00	7.275	41.21																					
60.00	7.155	39.50																					
64.00	7.035	37.69																					
68.00	6.915	35.78																					
72.00	6.795	33.77																					
76.00	6.675	31.66																					
80.00	6.555	29.55																					
84.00	6.435	27.44																					
88.00	6.315	25.33																					
92.00	6.195	23.22																					
96.00	6.075	21.11																					
100.00	5.955	19.00																					

CASING SPECIFICATIONS